



# PACKAGING / SHIPPING INFORMATION

SHAPE	DESCRIPTION	LBS. PER	PCS. PER	SQ. FT.	PCS. PER	LBS. PER	CTNS. PER
		SQ. FT.	SQ. FT.	PER CTN	PER CTN	CTN	PALLET
2x2	1-7/8 x 1-7/8	3.4	36	11	396	38	50
2x4	1-7/8 x 3-3/4	3.4	18	12	216	38	48
4x4	3-3/4 x 3-13/16	3.4	9	12	108	41	48
2x8	1-7/8 x 7-13/16	3.6	9	12	108	44	48
4x8	3-3/4 x 7-13/16	3.4	4.5	12	54	41	48
8x8	7-3/4 x 7-13/16	3.5	2.25	12	27	42	48
3x3	2-3/4 x 2-13/16	3.4	16	11	176	38	50
3x9	2-3/4 x 8-13/16	3.4	5.33	6.75	36	18	65
3x6	2-3/4 x 5-13/16	3.4	8	11	88	38	50
6x6	5-3/4 x 5-3/4	3.7	4	11	44	41	50
12x12	11-3/4 x 11-13/16	3.6	1	15	15	54	36
6x12	5-3/4 x 11-13/16	3.6	2	9	18	33	65
3x6 Bevel	2-3/4 x 5-13/16	3.6	8	10	80	36	50
3x9 Oval	2-3/4 x 8-13/16	3.6	5.33	4.88	26	18	90
EL Hex 3x6x8	3 x 6 x 8-13/16	3.5	4	12	48	39	50
8"Hex	7-3/8 x 8-3/8	4.4	3	9	27	40	48
12x24	12x24 13/16	3.75	.5	16	8	54	40

The standard thickness of all shapes is approx. 5/16 inch thick. Recommended grout joint - 1/4" (except 2"x2" and 2"x4" - 1/8")