

# Technical Specification

COLORMATCH™ Brick

**COLORMATCH Brick** is available in all Natural Hues, Color Wheel colors and Color-Match options. The ColorMatch Brick is stocked in 0190 Arctic White, 0790 Matte Arctic White, Sandstone, Gravel and Rose Gold.

Item# 9999472827 is used for all colors, Item# 9999472828 is used for specialty color Rose Gold

**Size: 2.5" x 7.5" | 48 pcs. per box | 37.5 lbs. per box | 7.11 sq. ft. per box | 6.75 pieces per SF**

**Sealing Tile:** It is recommended to seal prior to grouting with a penetrating sealer  
*Not recommended for (steam) shower wall installations*

**Tile Edge:** "Rustic" intentionally given a frayed or torn characteristic

**Surface Aesthetic:** Tile to be structurally sound but may have random drag lines, holes, and folds

**Setting and Grouting Materials:** Latex Portland cement, Mastic, or Epoxy. Care should be taken in grout color selection as tile surface will grout grab and may be very difficult to clean thoroughly.

**Cleaning:** Accomplished with PH neutral soap and water

**Nominal Size:** 2.5" x 7.5" Max / Min range  $\pm 4\%$ , (can range from 4% smaller to 4% larger)

Recommended Grout Joint: standard brick industry grout joint (3/8") or smaller grout joint - project permitting

## Testing Data

ColorMatch Brick is related to ANSI A137.1 Section 7 Specialty Tile  
Product is "Extruded", "Natural", Class E4, WALL Only

### Description

WARPAGE EDGE:

WARPAGE DIAGONAL:

WEDGING:

THICKNESS:

ABSORPTION:

COLOR UNIFORMITY:

CRAZING RESISTANT:

SCOF:

BREAKING STRENGTH:

FREEZE / THAW:

### Test Results

Max / Min range  $\pm 1.5\%$

Max / Min range  $\pm 1.5\%$

Max / Min range  $\pm 1.5\%$

.45" (~29/64th) , range .0625

7%-20%

V2 – V3 Slight to Moderate variation dependent on color choice

All colors are crazed and should be sealed.

Tile is not suitable for floor applications

80 LBF. Standard ceramic wall tile is 100 LBF-125 LBF

Not suitable for exterior installation in freeze thaw climates

### Fire Rating

CASSIFICATION IBC section 803

FLAME SPREAD zero

SMOKE DEVELOPED zero

Quarry Tile Co., 6328 East Utah Ave, Spokane, WA 99212 | ph: 800.423.2608 | fx: 509.536.4072