

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 24 Floor Tile*	(11-13/16" x 23-13/16") (30.00 cm x 60.50 cm)	5/16"	16.00	8
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	15.00	15
	6 x 12 Floor Tile	(5-3/4" x 11-13/16") (14.60 cm x 30.00 cm)	5/16"	9.00	18
	3 x 9 Floor Tile	(2-13/16" x 8-13/16") (7.10 cm x 22.40 cm)	5/16"	6.75	36
	8 x 8 Floor Tile	(7-13/16" x 7-13/16") (19.90 cm x 19.90 cm)	5/16"	12.00	27
	8" Hex Floor Tile	(8-5/8" x 7-1/2") (21.90 cm x 19.10 cm)	5/16"	9.00	27
	4 x 8 Floor Tile	(3-13/16" x 7-13/16") (9.60 cm x 19.90 cm)	5/16"	12.00	54
	2 x 8 Floor Tile	(1-7/8" x 7-13/16") (4.80 cm x 19.90 cm)	5/16"	12.00	108
	6 x 6 Floor Tile	(5-3/4" x 5-3/4") (14.60 cm x 14.60 cm)	5/16"	11.00	44
	3 x 6 Floor Tile	(2-13/16" x 5-13/16") (7.10 cm x 14.80 cm)	5/16"	11.00	88
	4 x 4 Floor Tile*	(3-13/16" x 3-13/16") (9.70 cm x 9.70 cm)	5/16"	12.00	108
	2 x 2 Floor Tile*	(1-7/8" x 1-7/8") (4.80 cm x 4.80 cm)	5/16"	11.00	396
	3 x 9 Oval Wall Tile	(2-13/16" x 8-13/16") (7.10 cm x 22.40 cm)	5/16"	4.88	26
	3 x 6 x 8 EL Hex Floor Tile	(3" x 5-7/8" x 7-7/8") (7.60 cm x 14.90 cm x 20.00 cm)	5/16"	12.00	48

Vision available in 8 x 8 and 12 x 12 only.

* Recommended for floor only

* Sizes available sheet-mounted and in custom patterns upon request.
 All colors are available with abrasive surface upon request.

APPLICATIONS

	Target DCOF Wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	✓*
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓***

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.





Gloss colors in all shapes and 3 x 9 Oval in all colors are recommended for wall applications only.

* Abrasive surface only

** 2 x 2 size only




*** 2 x 2, 4 x 4, 3 x 6 and 6 x 6 only

TRIM

	Number	Size	Number	Size
Surface Bullnose Runners 	Q1225	2 x 2	Q1445	4 x 4
	Q1285	2 x 8	Q1485	4 x 8
	Q1825	8 x 2	Q1845	8 x 4
	Q1365	3 x 6	Q1665	6 x 6
	Q1635	6 x 3	Q1885	8 x 8
	Q1395	3 x 9	Q11265	12 x 6
Q1935	9 x 3	Q16125	6 x 12	
Q1485 Illustrated				
Surface Bullnose Corners 	QC1225	2 x 2	QC1445	4 x 4
	QCR-L1285	2 x 8	QCR-L1485	4 x 8
	QCR-L1365	3 x 6	QC1665	6 x 6
	QCR-L1395	3 x 9	QC1885	8 x 8
			QCR-L11265	12 x 6
			QCR-L1395 Oval	3 x 9
QC1445 Illustrated				
Cove Base Flat Top 	Q3666	5 x 6		
	Q3686	5 x 8		
	Q36126	5 x 12		
Q3666 Illustrated				
Cove Base Round Top 	Q3665	6 x 6		
	Q3685	6 x 8		
	Q36125	6 x 12		
Q3685 Illustrated				

Left and Right Corners are also available for most bullnose and cove base items.

CORNER TRIM

Outside Corners	Quarter Round	Quarter Cove
		
QC3666 6" Flat Top	QC3665 6" Round Top	Q106 (6")
		Q107 (6")

NATURAL HUES

	Munsell	LRV Illuminate-OBS: F02-02 (CWF)
QH02	9.3YR 8.3/1.6	66.58
QH09	9.4R 5.8/11/3	58.70
QH10	2.5Y 7.3/1.5	48.08
QH12	3.7GY 5.7/1.9	58.25
QH13	5.1R 4.0/9.3	40.13
QH14	4.8R 4.2/9.7	42.71
QH15	4.4GY 7.2/0.4	45.76
QH16	1.1Y 5.9/1.5	29.42
QH22	6.8G 7.2/1.2	73.39
QH24	7.7Y 8.5/0.9	68.60
QH29	2.0G 4.7/4.4	15.85
QH30	4.1GY 7.3/6.8	47.64
QH32	0.6B 3.9/0.4	11.10
QH33	5.2Y 8.8/0.9	75.91
QH34	8.5BG 5.4/1.2	55.93
QH35	0.6B 3.9/0.4	11.10
QH36	6.2Y 8.7/0.8	87.76
QH41	3.7B 5.5/4.4	22.91
QH43	3.5PB 4.0/4.1	11.11
QH44	2.7PB 5.5/6.2	23.30
QH45	0.9RP 2.8/0.2	5.76
QH46	7.3PB 3.1/4.3	6.62
QH47	1.5R 3.3/3.3	8.06
QH48	8.8Y 8.9/0.1	76.15
QH54	5.2P 3.7/2.3	9.81
QH57	7.5PB 3.1/1.2	7.02
QH61	0.4PB 3.7/4.3	8.67
QH63	0.3GY 9.2/0.2	82.66
QH65	2.8RP 2.6/0.1	4.87
QH66	6.6B 3.8/2.9	9.81
QH68	8.7B 5.2/3.4	20.33
QH71	2.9YR 5.9/8.1	30.96
QH73	9.0YR 6.7/7.5	41.20
QH74	1.2YR 4.4/6.0	15.69
QH80	5.7GY 6.4/5.9	34.39
QH82	9.7B 6.9/2.6	40.43
QH83	8.2Y 8.8/0.7	75.38
QH84	1.7Y 7.3/1.6	48.64
QH95	8.8R 5.6/12.1	27.26
QH97	2.6Y 7.8/9.2	59.27

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/4" 2 x 2 & 2 x 4: 1/8"	 Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 6.0%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	5.0 - 7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance		
1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



Healthy Homes | Healthy Planet

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2020 Daltile (9/20)