

VISION on NATURAL HUES™

ECO-BODY CERAMIC

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/4" 2 x 2 & 2 x 4: 1/8"	 Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 6.0%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	5.0 - 7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance		
1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

 **PRE-CONSUMER RECYCLED MATERIALS**  **MADE IN THE U.S.A.**

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

ZEROTOX

Healthy Homes | Healthy Planet™

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.


IMAGINE WHAT'S POSSIBLE™

NATURAL HUES COLORS

	Munsell	LRV Illuminate-OBS: F02-02 (CWF)
QH02	9.3YR 8.3/1.6	66.58
QH09	9.4R 5.8/11/3	58.70
QH10	2.5Y 7.3/1.5	48.08
QH12	3.7GY 5.7/1.9	58.25
QH13	5.1R 4.0/9.3	40.13
QH14	4.8R 4.2/9.7	42.71
QH15	4.4GY 7.2/0.4	45.76
QH16	1.1Y 5.9/1.5	29.42
QH22	6.8G 7.2/1.2	73.39
QH24	7.7Y 8.5/0.9	68.60
QH29	2.0G 4.7/4.4	15.85
QH30	4.1GY 7.3/6.8	47.64
QH32	0.6B 3.9/0.4	11.10
QH33	5.2Y 8.8/0.9	75.91
QH34	8.5BG 5.4/1.2	55.93
QH35	0.6B 3.9/0.4	11.10
QH36	6.2Y 8.7/0.8	87.76
QH41	3.7B 5.5/4.4	22.91
QH43	3.5PB 4.0/4.1	11.11
QH44	2.7PB 5.5/6.2	23.30
QH45	0.9RP 2.8/0.2	5.76
QH46	7.3PB 3.1/4.3	6.62
QH47	1.5R 3.3/3.3	8.06
QH48	8.8Y 8.9/0.1	76.15
QH54	5.2P 3.7/2.3	9.81
QH57	7.5PB 3.1/1.2	7.02
QH61	0.4PB 3.7/4.3	8.67
QH63	0.3GY 9.2/0.2	82.66
QH65	2.8RP 2.6/0.1	4.87
QH66	6.6B 3.8/2.9	9.81
QH68	8.7B 5.2/3.4	20.33
QH71	2.9YR 5.9/8.1	30.96
QH73	9.0YR 6.7/7.5	41.20
QH74	1.2YR 4.4/6.0	15.69
QH80	5.7GY 6.4/5.9	34.39
QH82	9.7B 6.9/2.6	40.43
QH83	8.2Y 8.8/0.7	75.38
QH84	1.7Y 7.3/1.6	48.64
QH95	8.8R 5.6/12.1	27.26
QH97	2.6Y 7.8/9.2	59.27

APPLICATIONS

	Target DCOF Wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	✓*
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓***

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Gloss colors in all shapes and 3 x 9 Oval in all colors are recommended for wall applications only.

* Abrasive surface only

** 2 x 2 size only

*** 2 x 2, 4 x 4, 3 x 6 and 6 x 6 only